

# NATIONAL AEROSPACE STANDARD



© COPYRIGHT 2011 AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC. ALL RIGHTS RESERVED

FED. SUPPLY CLASS 53GP

#### FOREWORD

This standard sets forth a standard test method for torque testing threaded fasteners.

#### AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC TABLE OF CONTENTS Paragraph Sheet SCOPE 2 1. 1.1 2 Applicability 2 2 **REFERENCED DOCUMENTS** 2.1 2 Government documents 1000 WILSON BLVD. ARLINGTON, VA 22209 2.1.1 Specifications, standards and handbooks 2 2.1.2 Other Government documents, drawings, and publications 2 3 3. DEFINITIONS 3 3.1 Lock area 3 **Torque terms** 3.2 4. GENERAL REQUIREMENTS 3 3 4.1 Torque apparatus 3 **Torque wrenches** 4.1.1 3 Power tools 4.1.2 4.1.3 **Torsion machines** 3 3 4.1.4 Test fixtures 3 Specimens 4.1.5 4 5. DETAIL REQUIREMENTS 4 5.1 Test procedures Self-locking torque 4 5.1.1 Assembly torque 4 5.1.2 THIS DRAWING SUPERSEDES ALL ANTECEDENT STANDARD DRAWINGS FOR THE SAME PRODUCT AND SHALL BECOME EFFECTIVE NO LATER THAN SIX MONTHS FROM THE LAST REVISION DATE. 4 5.1.3 Maximum self-locking torque at installation 4 5.1.4 Breakloose torque Δ Breakaway torque 5.1.5 5.1.6 Minimum self-locking torque 4 Multiple tests 4 5.1.7 4 Wrench torque 5.1.8 Torque-out 5 5.1.9 5 5.1.9.1 Test to specified proof torque 5 5.1.9.2 Ultimate torque test 5 Torque test for threaded inserts-internal threads only 5.2 5 6. NOTES 5 Test Report 6.1 FIGURE Sheet Figure 6 Test fixture 1. (1)COMPLETELY REVISED THE INITIAL RELEASE OF THIS DOCUMENT SUPERSEDES MIL-STD-1312-31. DESIGNATION FOR THIS TEST METHOD REMAINS MIL-STD-1312-31. THIRD REVISION CUSTODIAN ANGLE Ð 1 NATIONAL AEROSPACE STANDARDS COMMITTEE PROJECTION CLASSIFICATION TITLE PROCUREMENT 09-01 STANDARD PRACTICE SPECIFICATION FASTENER TEST METHODS NASM1312-31 FORM METHOD 31 NONE TORQUE SHEET 1 OF 6

LISE OF OR DEFITANCE UPON THIS DOCUMENT OR ANY NATIONAL AEROSPACE STANDARD IS ENTIRELY VOLUNTARY. AIA DOES NOT QUALIFY SUPPLIERS OR CERTIFY Copyright Aerospace Industries Association of America Inc., MS PRODUCED UNDER NATIONAL AEROSPACE STANDARD: Sold to INFORMATION HANDLING SERVICES, 01874946 DESPECTING (1) THE SUITABILITY OF No reproduction or networking permitted without licenses from IHS 'R APPLICATION OR (2) THE EXISTENCE OF OR APPLIC Not for Resale, 2011/9/1 16:57:21 GMT 'K TRAUETINGS RIGHTS.





REVISION

NASM1312-31

SHEET 2

© COPYRIGHT 2011 AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC. ALL RIGHTS RESERVED

### 1. SCOPE

1.1 <u>Applicability</u>. This test method describes the test procedure for determining room temperature transmission and locking torque of threaded fasteners.

### REFERENCED DOCUMENTS

#### 2.1 <u>Government documents</u>

2.1.1 <u>Specifications, standards and handbooks</u>. Unless otherwise specified, the following specifications, standards and handbooks of the issue listed in the current Department of Defense Index of Specifications and Standards (DoDISS) and the supplement thereto (if applicable), form a part of this standard to the extent specified herein.

SPECIFICATION

<u>Military</u> A-A-59309 Tester, Torque Wrench

2.2 <u>Other publications</u>. The following document(s) forms a part of this specification to the extent specified herein. The issue of the documents which are indicated as DOD adopted shall be the issue in the currents DoDISS and the supplement thereto, if applicable.

PURCHASE DESCRIPTION

 SAE International

 AS1310
 Fastener Torque for Threaded Applications, Definitions Of

(Application for copies should be addressed to SAE INTERNATIONAL, 400 Commonwealth Drive, Warrendale, PA 15096.)

STANDARDS

Aerospace Industries Association (AIA) NASM1312 Fastener Test Methods

(Application for copies should be addressed to the Aerospace Industries Association, 1000 Wilson Boulevard, Suite 1700, Arlington, VA 22209.)

SPECIFICATION

ASME ASME B107.300 Torque Instruments (Mechanical)

(Application for copies should be addressed to ASME, Three Park Avenue, New York, NY 10016-5990.)

(Copies of specifications, standards, handbooks, drawings and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

(1) COMPLETELY REVISED

LISE OF OR REI JANCE UPON THIS DOCUMENT OR ANY NATIONAL AEROSPACE STANDARD IS ENTIRELY VOLUNTARY. AJA DOES NOT QUALIFY SUPPLIERS OR CERTIFY Copyright Aerospace Industries Association of America Inc., MS PRODUCED UNDER NATIONAL AEROSPACE STANDARD: Sold to M DEDBECENTATION OF 1 ATM DESPECTING (1) THE SUITABILITY OF Provided by IHS under license with AlANAS No reproduction or networking permitted without license from IHS 'R APPLICATION OR (2) THE EXISTENCE OF OR APPLIC Not for Resale, 2011/9/1 16:57:21 GMT 'S UNDUCTIVANS RIGHTS.

2.

FORM 09-01



3.

4.

4.1



REVISION

NASM1312-31

SHEET 3

© COPYRIGHT 2011 AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC. ALL RIGHTS RESERVED

## DEFINITIONS

- 3.1 <u>Lock area</u>. Lock area is the area where the self-locking feature applies to either the externally threaded or internally threaded member of the fastener.
- 3.2 <u>Torque terms</u>. Torque terms shall be as defined in AS1310.

## GENERAL REQUIREMENTS

#### <u>Test apparatus</u>

- 4.1.1 <u>Torque wrenches</u>. Torque wrenches shall be in accordance with ASME B107.300, Type I, Class A and certified to A-A-59309. Torque wrenches shall have been calibrated within 12 months for production testing and within 3 months for qualification testing. Torque wrenches shall be selected so that torque values are within twenty percent and ninety percent of the torque wrench capacity. If the torque values are not within the limits, the test shall be repeated with an appropriate torque wrench.
- 4.1.2 <u>Power tools</u>. Pneumatic, reversible drivers shall be calibrated at the beginning of the test to the accuracy specified herein. Power tools shall be adjusted to produce torques as specified in the procurement specification within  $\pm 3$  inch-pounds or  $\pm 5$  percent, whichever is greater. The maximum allowable speed shall be 500 rpm.
- 4.1.3 <u>Torsion machines</u>. Torsion machines shall be accurate within ± 2 percent. Torsion machines shall have been calibrated within 12 months for production testing and within 3 months for qualification testing. The torque indicating scale of the torsion machine shall be selected so that indicated torque readings are within 10 percent and 90 percent of the scale capacity. If the torque values are not within the limits, the test shall be repeated using an appropriate scale.
- 4.1.4 <u>Test fixtures</u>. The construction of the test fixtures shall be such that the torque required to overcome friction through the wrench holding device does not exceed 1 inch-ounce for wrench capacity up to 300 inch-pounds, and 3 inch-ounces for larger wrench capacities.

The concentricity between the torquing device and the fastener shall be within .010 inch FIM (full indicator movement). The plane of the torquing shall be perpendicular to the axis of the fastener within 3 degrees. A typical fixture is shown in Figure 1.

4.1.5 <u>Specimens</u>. The fasteners shall be as specified in the procurement specification. If all the fastener test members are not specified, the fastener elements normally used with the fastener being tested shall be used.

Unless otherwise specified, a single fastener test member shall be used for all cycles of one torque test.

Unless specified otherwise, no supplementary lubrication shall be used. Cadmium and silver plating are not considered to be lubricants when used as the final coating.

Reduced or selected tolerance test members are not recommended if the test result does not represent actual application values.

1) COMPLETELY REVISED



THIS DRAWING SUPERSEDES ALL ANTECEDENT STANDARD DRAWINGS FOR THE SAME PRODUCT AND SHALL BECOME EFFECTIVE NO LATER THAN SIX MONTHS FROM THE LAST REVISION DATE.

09-01

FORM



AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC

THIS DRAWING SUPERSEDES ALL ANTECEDENT STANDARD DRAWINGS FOR THE SAME

# NATIONAL AEROSPACE STANDARD



© COPYRIGHT 2011 AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC. ALL RIGHTS RESERVED

	5.	DETAIL REQUIREMENTS		
1000 WILSON BLVD. ARLINGTON, VA 22209	5.1	Test procedures		
	5.1.1	<u>Self-locking torque</u> . The fastener elements shall be assembled in a manner that will ensure that the externally threaded member protrusion beyond the internally threaded member lock area (see 3.1) will range from a minimum of chamfer breakthrough to a maximum of five thread pitches plus chamfer.		
		Torque shall be applied to the assembly in a manner that will ensure that all torque is transmitted to the mating element before axial load is applied.		
	5.1.2	Assembly torque. When specified in the specification, assembly torques shall be applied in a manner that will produce axial load in the fastener.		
	5.1.3	<u>Maximum self-locking torque at installation</u> . Maximum self-locking torque is the maximum torque encountered during assembly of the elements to the thread lock protrusion condition referenced above before axial load is applied.		
	5.1.4	<u>Breakloose torque</u> . Initiate removal cycle, stopping after axial load is relieved, when applicable. The torque encountered after disengagement is "breakloose torque."		
	5.1.5	Breakaway torque. Re-initiate removal cycle. Minimum or maximum breakaway torque is the torque necessary to initiate removal from the breakloose torque position.		
	5.1.6	Minimum self-locking torque. Minimum self-locking torque shall be recorded after breakaway torque is determined while the fastener is in motion and engaged with 100 percent of the locking feature.		
	5.1.7	<u>Multiple tests</u> . When locking torque characteristics must be determined for more than one assembly and removal cycle, the procedure in 5.1.1 shall apply with the following exceptions when specified in the procurement specification.		
PRODUCT AND SHALL BECOME EFFECTIVE NO LATER THAN SIX MONTHS FROM THE LAST REVISION DATE.		a. Power tools adjusted to deliver the assembly torques and capable of installation/removal rates (rpm) as specified in the procurement specification shall be used for all cycles except the observation cycle. Speed shall not exceed 500 rpm.		
		b. The interval over which the torque observation cycle is monitored shall be as specification.	al over which the torque observation cycle is monitored shall be as specified in the product on.	
		c. The fastener elements shall be allowed to cool after installation and removal.		
		d. For lubricated fasteners, the amount or duration of cooling is not controlled.		
	e. For unlubricated fasteners whose torque has been applied by high speed (500 rpm max) equipment, compressed air shall be used to cool the fasteners after installation and removal for the following durat		n max) equipment, or the following durations:	
		(1) not less than 5 seconds for fastener diameters up to 5/16;		
		(2) not less than 10 seconds for fastener diameters between 5/16 and 9/16;		
		(3) not less than 15 seconds for fastener diameters above 9/16.		
	5.1.8	5.1.8 Wrench torque. The wrench torque test shall be conducted in a test fixture as shown in Figure 1 using appropriate assembly tools to fit the wrenching configuration. Torque shall be applied to the test fastener at a uniform rate (20 in-lb/sec max). Unless otherwise specified in the specification, no end load may be applied to the driving tool. The limit of torque transmission (wrench torque) shall be the maximum torque that can be obtained without fastener failure or damage to the wrenching tool or fastener wrenching configuration to the extent that they are no longer functional.		
1			REVISION	
RM 09-0			NASM1312-31	
<u>Q</u>			SHEET 4	

Copyright Aerospace Industries Association of America Inc. MS PRODUCED UNDER NATIONAL AEROSPACE STANDARD IS ENTIRELY VOLUNTARY. AIA DOES NOT QUALIFY SUPPLIERS OR CERTIFY Provided by IHS under license with AIA/NAS

ASSOCIATION



REVISION

NASM1312-31

SHEET 5

© COPYRIGHT 2011 AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC. ALL RIGHTS RESERVED

- 5.1.9 <u>Torque-out</u>. The torque-out test will determine the torsional stability of nuts designed for permanent attachment to the structure. The nuts shall be assembled in the specified test plate. Torque shall be applied at a uniform rate (20 in-lb/sec max) so that no axial load is induced in the nut element.
- 5.1.9.1 <u>Test to specified proof torque</u>. When specified test torques are to be verified, the internally threaded assembly shall be subjected to the specified values first in the clockwise direction, then in the counterclockwise direction. The procedure shall be reversed for left hand threads.
- 5.1.9.2 <u>Ultimate torque test</u>. The ultimate torque test shall determine maximum torque that can be developed without rupture or deformation sufficient to prevent normal use of the nut. Torque shall be applied in the counterclockwise direction using a screw or stud extraction tool applied to the top of the assembly. Caution must be exercised to prevent applying a load to the bearing surface of the nut.
- 5.2 <u>Torque test for threaded inserts-internal threads only</u>. Apparatus and test procedures defined herein shall be used to test the internal threads. Tests to determine the torsional stability of the external threads shall be performed as described in the procurement specification.

#### 6. NOTES

- 6.1 <u>Test report</u>. The test report shall include the following data:
  - a. Fastener description.
    - 1. Part number.
      - 2. Lot identification.
      - 3. Material.
      - Heat treat.
      - 5. Grip length.
      - 6. Mating part.
      - 7. Lubrication or plating.

### b. Test machine.

- 1. Model and serial number.
- 2. Calibration date.

#### c. Torques.

- 1. Max. self-locking torque at installation.
- 2. Assembly torque.
- 3. Breakloose torque.
- 4. Breakaway torque.
- 5. Min. self-locking torque at removal cycle.
- d. Test method.
- e. Test load.
- f. Type of failure.
- g. Results.
- h. Specimen preparation.

# 1) COMPLETELY REVISED

LISE OF OR RELITANCE UPON THIS DOCUMENT OR ANY NATIONAL AEROSPACE STANDARD IS ENTIRELY VOLUNTARY. AIA DOES NOT QUALIFY SUPPLIERS OR CERTIFY Copyright Aerospace Industries Association of America Inc. MS PRODUCED UNDER NATIONAL AEROSPACE STANDARD STATE MARKET ATTAIN ON CLAIM DESPECTING (1) THE SUITABILITY OF Provided by IHS under license with AIA/NAS CONCENTRATION OF CLAIM DESPECTING (1) THE SUITABILITY OF No reproduction or networking permitted without license from IHS'R APPLICATION OR (2) THE EXISTENCE OF OR APPLIC Not for Resale,2011/9/116:57:21 GMT/K LIKAUE/IMAKS RIGHTS.

THIS DRAWING SUPERSEDES ALL ANTECEDENT STANDARD DRAWINGS FOR THE SAME PRODUCT AND SHALL BECOME EFFECTIVE NO LATER THAN SIX MONTHS FROM THE LAST REVISION DATE.

09-01

FORM

AEROSPACE INDUSTRIES

# NATIONAL AEROSPACE STANDARD

© COPYRIGHT 2011 AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC. ALL RIGHTS RESERVED





LISE OF OR REI TANCE UPON THIS DOCUMENT OR ANY NATIONAL AEROSPACE STANDARD IS ENTIRELY VOLUNTARY. ATA DOES NOT QUALIFY SUPPLIERS OR CERTIFY Copyright Aerospace Industries Association of America Inc. MS PRODUCED UNDER NATIONAL AEROSPACE STANDARD: ATA MAKES NO DEDECEMENTATION OF CLAIM DESPECTING (1) THE SUITABILITY OF Provided by IHS under license with AIA/NAS THE MS PRODUCED UNDER NATIONAL AEROSPACE STANDARD: NOT PROVIDE ASSOCIATION OF CLAIM DESPECTING (1) THE SUITABILITY OF No reproduction or networking permitted without license from IHS R APPLICATION OR (2) THE EXISTENCE OF OR APPLIC Not for Resale.2011/9/1 16:57:21 GMT IN UNDER ARIGHTS.